

## Technical Specification/ **Product Datasheet**

Clark-Drain Ltd., Station Road, Yaxley. Peterborough, PE7 3EQ. England.



CD 261/SF CD 262/SF CD 263/SF CD 264/SF CD 265/SF Specific Product Code/s:

**Product Group:** Composite Manhole Covers

Sub-Category: B125 Solid-Top Manhole Covers for Pavements & Driveways

Material Grade/s: Cover = **Sheet Moulded Compound** 

> Frame = Mild Steel to BS EN 1449:1991/EN 10025:2004

> > Galvanising to BS EN 1461:2009

Basic Dimensions (mm): Clear-Opening **Overall Size** Depth, inset Depth, overall CD 261/SF 300 x 300 401.5 x 401.5 110 70 CD 262/SF 450 x 300 551.5 x 401.5 70 110 CD 263/SF 450 x 450 551.5 x 551.5 70 110 70 CD 264/SF 600 x 450 701.5 x 551.5 110 70 CD 265/SF 600 x 600 701.5 x 701.5 110

Weight (kgs): Overall Cover CD 261/SF 10 6.5 CD 262/SF 13.5 9.5

CD 263/SF 12 17 CD 264/SF 21.5 15 CD 265/SF 28 21

Frame Pressure

CD 261/SF 3.2 Bearing Area (N/mm²):

CD 262/SF 2.5 CD 263/SF 2.1 CD 264/SF 1.8 CD 265/SF 1.5

Load Rating Classification: B125 (12.5 tonnes)

Polished Skid-Resistance Value (PSRV):

60

Features:

- Integral lifting key holes (to suit CD 553 or CD 553L lifting keys, available separately) with cover-caps to reduce debris ingress
- Fully galvanised steel frame with 70mm inset depth to suit tarmac, concrete or paved areas
- Non-ferrous composite cover, resistant to chemicals, deformation, rust and corrosion
- Supplied fitted with locking screws
- Frame skirt provided with fixing holes to securely attach frame to
- Perfect partners for Clark-Drain B125 polypropylene chambers
- All covers marked with "Traffic Signals / Street Lighting"
- Frame is fitted with lugs for casting into concrete

Date Issued: 05/11/19