

TECHNICAL SPECIFICATION



5m Adjustable Work Positioning Lanyard with Rope Grab

5m Adjustable Work Positioning Lanyard with Rope Grab / FAR0421



DESCRIPTION

5m work positioning lanyard with non-openable aluminium rope grab with 2 screw gate connectors in alloy steel. Rope ends stitched and covered with polyethylene protective sleeve.

OPTIONS

5m Adjustable Work Positioning Lanyard with Rope Grab (FAR0421)

SAFETY STANDARDS

EN 358



SPECIFICATIONS

Length
5m Max.

Rope Ends
Stitched and Covered With Polyethylene Protective Sleeve. Abrasion Resistant Thimbles Provided Within Loops

Adjustment Device
Non Openable Rope Grab Aluminium

Delivered With
2 Screwgate Connectors In Alloy Steel. Gate Opening 18mm. Conforms To EN 362 Class B & M

Material
12mm High Quality Kermantle Rope

Protective Rope Sleeve
60cm



Product Weight
1170g

APPLICATIONS

General guidance only and should not be considered a substitute for a full risk assessment

Glazing

Roofing

Wind Turbines

DOWNLOADS

 [Image Pack \(ZIP\)](#)

 [doc-far0420-far0421.pdf \(PDF\)](#)

