HyFlex™

11-427

Designed to make the selection of hand protection easy

Previously known as: Puretough™P3000TROPIQUE

Heat | Medium Duty

Abrasion-resistant medium-duty safety gloves, offer wearers heat and cut resistance

- **Improved durability:** HyFlex™ 11-427 are medium-duty gloves with a durable foam nitrile coating that meets EN and ANSI/ISEA 105-2024 ABRASION LEVEL 4 standards
- **Increased eco-friendliness:** Their PU/nitrile coating is made using a more environmentally conscious water-based process
- **Reduced surface defect risks:** Their silicone-free design eliminates the risk of related contaminant transfer to metal when painting
- **Minimized health risks:** These HyFlex™ gloves' DMF-free formulation prevents potential health risks
- **Enhanced defenses:** Their high-visibility, high-performance fibers ensure contact heat resistance up to 100°C/212°F
- **Easy identification:** The orange color-coded indicator button signifies that these gloves meet ANSI/ISEA 105-2024 CUT A2 and EN ISO B standards



Industries

- Automotive

Applications

- Production line support & maintenance
- Product shipping, transport and delivery
- Loading and unloading trucks and vehicles
- Loading trucks & vehicles
- Maintenance
- Lock smith
- Handling metal sheets & panels
- Handling parts with sharp, rough edges
- Handling incoming goods
- Handling outgoing goods: cans, vessels, bulkpack and cartons
- Applying sealers, touching up

HyFlex™

11-427

Designed to make the selection of hand protection easy

Previously known as: Puretough™P3000TROPIQUE

Key Features

- **Foam nitrile coating:** Durable, but more eco-conscious
- **DMF- and silicone-free:** Fewer health risks, suited to spray-painting
- **High-visibility, high-performance fibers:** Heat* and cut resistance *contact heat resistance up to 100°C/212°F

Technologies

INTERCEPT™
Cut Resistance Technology

Vulcanization Chemical Accelerators

- Natural rubber proteins (in knitwrist elastic)
- Zinc Diethyldithiocarbamate

Only a very small number of users may be sensitive to this ingredient(s) and hence may develop irritant and/or allergic contact reactions.

Performance Standards & Regulatory Compliance

CE

ANSI/ISEA 105-2024
A2
4 3

EN388: 2016
4X32B

EN 407
X1XXXX

Specifications

BRAND | STYLE	DESCRIPTION	Gauge	SIZE	LENGTH	COATING COLOR	PACKAGE
HyFlex™ 11-427	**Finishing**: 3/4 Coated **Coating Material**: Foam Nitrile **Liner Material**: Polyamide, INTERCEPT™ Cut Resistance Technology **Cuff Style**: Knitwrist	13	7, 8, 9, 10, 11	235-260 mm / 9.25-10.23 inches	Grey	• 12 pairs/bag, 12 bags/carton

Ansell