

Product data sheet uvex silv-Air 2100 FFP1 NR D



Product information

Product features	<ul style="list-style-type: none">• Particle-filtering cup shape mask without valve• Protection level FFP1• Soft material edges for high wearing comfort• Continuous head band for a comfortable and secure fit• Flexible and adjustable nose clip• Compatible with uvex safety eyewear• Soft sealing lip guarantees a secure, comfortable sealed position of the mask• Mask fulfils the requirements of the dolomite dust test (D)
Materials	Headband: textile Nose clip: aluminum Filter/mask: Melt Blown PP, Polyester Sealing lip: PVC foam
Weight	12 g
Standard	EN 149:2001 + A1:2009

Versions

Article number	Colour/Version	Retail unit
8762100	cup shape mask FFP1, white without valve	20 pcs. per box
8742101	cup shape mask FFP1, white without valve	3 pcs. per bag

Packaging sizes

Box	approx. 135 x 135 x 230 mm
Outer Carton	approx. 560 x 430 x 260 mm

Maximum breathing resistance acc. to EN149 in mbar

	Inhalation resistance 30l/min.	Inhalation resistance 95l/min.	Exhalation resistance 160l/min.
FFP1	0,6	2,1	3,0
FFP2	0,7	2,4	3,0
FFP3	1,0	3,0	3,0

Areas of use*

The respiratory protection mask can be used against solid, aqueous and non-volatile liquid aerosols up to 4 times the respective limit values.	Particles (neither toxic nor associated with fibrosis), Agriculture, hay, food industry, grain, flour, graphite, chalk, marble, rust.
---	---

*Please note that the above mentioned areas of use are examples only. The selection of PPE needs to be carried out by a competent person, in conjunction with relevant and current legislation.

All respiratory protective devices fall into PPE category III (high risks).

Uvex accepts no liability for any possible harm or damage which may result from this information.
This data sheet does not replace a detailed risk assessment nor seeking specialist advice.