

3 AA BATTERIES

XPP-5418GX/RX-K01

INTRINSICALLY SAFE FLASHLIGHT

**NIGHTSTICK**<sup>®</sup>  
Life Depends on Light<sup>™</sup>

IP-X7  
WATER  
PROOF



Large, textured button that is  
**easy-to-use with gloves**



Durable polymer body is  
**impact & chemical resistant**



**Non-conductive body** for  
hazardous environments



Sharp focused flashlight beam  
for **distance illumination**



AVAILABLE IN MULTIPLE COLORS

XPP-5418RX-K01

200 LUMENS



# INTRINSICALLY SAFE FLASHLIGHT

## 3 AA BATTERIES (not included)

### ITEM NUMBER/UPC

- XPP-5418GX-K01, UPC 0 17398 80620 6
- XPP-5418RX-K01, UPC 0 17398 80622 0

### MARKET APPLICATIONS

- Hazardous work environments, industrial, automotive, fire and rescue

### CERTIFICATIONS

- cETLus, ATEX, IECEX, CE, NFPA, InMetro

### CASE MATERIAL

- Engineered polymer

### FLASHLIGHT LUMENS/RUNTIME

- 200L, 10.5 hrs. runtime

### CANDELA

- 5,129

### BEAM DISTANCE

- 143 m

### WATER RATING

- ANSI IP-67 dustproof / waterproof

### DROP RATING

- 2 meters

### DIMENSIONS

- LENGTH: 5.6 in (142 mm)
- HANDLE DIAMETER: 0.75 in x 1.4 in (19 mm x 35 mm)
- HEAD DIAMETER: 1.5 in (38 mm)
- WEIGHT: 5.4 oz (153 g)

### POWER SOURCE

- AA batteries (not included)

### WARRANTY

- Limited lifetime

### WHAT'S INCLUDED

- Flashlight
- Multi-angle mount with hardhat slot and brim mounts

FL 1 STANDARD		
		
		

**Bayco Products, Inc. XPP-5418GX/RX**  
**640 S. Sanden Blvd., Wylie, TX 75098**

Ex ia FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS

<p>CLASS I DIV 1 GRPS A-D T3</p> <p>CLASS II &amp; III DIV 1 GRPS E-G T135°C</p> <p>CLASS I ZONE 0 AEx ia IIC T3 Ga</p> <p>Ex ia IIC T3 Ga</p> <p>© II 1 G Ex ia op is IIC T3 Ga</p>	<p>Ex ia op is IIC T3 Ga</p> <p>Intertek ITS 13 ATEX27837X</p> <p>IECEX ITS 16.0067X</p> <p>-20°C ≤ Tamb ≤ +40°C</p> <p>1.5V/Cell with three in series</p> <p>Energizer E91 or EN91</p>
--	---

WARNINGS:  
 Replace batteries in a non-hazardous location.  
 Use only Energizer AA Model E91 or EN91 batteries.

AVERTISSEMENT:  
 Remplacer les piles dans une zone non dangereuse.  
 Utiliser uniquement les piles Energizer AA - modèle E91 ou EN91.

CE 2575

Segurança  
  
 INMETRO OCP 0034  
 Ex ia op is IIC T3 Ga  
 1.5V x 3 = 4.5V  
 NCC 15.0288 X

**CERTIFIED**

     