

878 Best® Butyl



Unsupported Butyl coating

DESCRIPTION

- Fully coated
- Rolled cuff
- Standard finish
- Without special treatment
- Anatomical shape
- Available by individual pair in polybag with eyelet



BENEFITS

- A thin, light glove with a "second skin" feel
- Protects the hand from a wide array of chemical hazards (more information on www.chemrest.com)
- Impermeable for working in damp or greasy environments
- Cuff prevents dirt from entering the glove
- Lower allergy risks
- Designed for easy movement and continuous wear
- Packaging that helps finding the right model in displays
- Wrist well protected
- Low-soil colour

RECOMMENDED FOR THESE RISKS:

Chemicals

RECOMMENDED FOR THESE LINES OF WORK:

Chemical industry / Acid components

Police & Army

Chemical industry / Acetone and Ketone components

AVAILABLE SIZES

8/M • 9/L • 10/XL • 11/XXL

LENGTH

Dependent on size, in mm (flat)

350

PACKAGING

Pairs or pieces per pack/box

1/12

COLOUR OF SUPPORT/COATING

Black

THICKNESS

in mm

0,70

RECOMMENDATIONS FOR USE

- Store away from light and humidity
- Rinse the gloves in running water before removing, using a neutral detergent if necessary
- Do not wear gloves when there is a risk of entanglement by moving parts of machines.
- Potential allergens: thiazoles and thiurames

89/686/CEE Cat.III	EN 388 - 2003	ABRASION 0 1 2 3 4	CUTTING 0 1 2 3 4 5	EN 374-2 - 2003	EN 374-3 - 2003	B - ACETONE 0 1 2 3 4 5 6	I - ETHYL ACETATE 0 1 2 3 4 5 6
		TEARING 0 1 2 3 4	PUNCTURE 0 1 2 3 4			K - CAUSTIC SODA 40% 0 1 2 3 4 5 6	
0123	1121				BIK		



The
Safety Supply
Company

[Updated 13/10/11]