

892 Best® Viton® II



Unsupported Viton over Butyl coating

DESCRIPTION

- Fully coated
- Rolled cuff
- Standard finish
- Without special treatment
- Anatomical shape
- Available by individual pair in polybag with eyelet



RECOMMENDED FOR THESE RISKS:

Cuts

RECOMMENDED FOR THESE LINES OF WORK:

Petrochemistry

BENEFITS

- A thin, light glove with a "second skin" feel
- Protects the hand from a wide array of chemical hazards (more information on www.chemrest.com)
- Impermeable for working in damp or greasy environments
- Cuff prevents dirt from entering the glove
- Lower allergy risks
- Designed for easy movement and continuous wear
- Packaging that helps finding the right model in displays
- Wrist well protected
- Low-soil colour

AVAILABLE SIZES

7/S • 8/M • 9/L • 10/XL • 11/XXL

LENGTH

Dependent on size, in mm (flat)

300

PACKAGING

Pairs or pieces per pack/box

1/12

COLOUR OF SUPPORT/COATING

Black

THICKNESS

in mm

0,30

RECOMMENDATIONS FOR USE

- Store away from light and humidity
- Rinse the gloves in running water before removing, using a neutral detergent if necessary
- Do not wear gloves when there is a risk of entanglement by moving parts of machines.
- Potential allergens: thiazoles and thiurames

89/686/CEE
Cat. III



0123

EN 388 - 2003



2000

ABRASION

0 1 2 3 4

TEARING

0 1 2 3 4

CUTTING

0 1 2 3 4 5

PUNCTURE

0 1 2 3 4

EN 374-2 - 2003



EN 374-3 - 2003



DFL

D - DICHLOROMETHANE F - TOLUENE

0 1 2 3 4 5 6 0 1 2 3 4 5 6

L - SULPHURIC ACID 96

0 1 2 3 4 5 6



The
Safety Supply
Company