

PRODUCT SPECIFICATION & TECHNICAL DATASHEET

PG54 - Endurance Glowtex Helmet

Collection: Head Protection Range: PPE Materials: ABS Outer Carton: 20

Product information

Endurance helmet with 6-point textile harness and wheel ratchet adjustable size 56-63cm. The ABS shell is made with special photo-luminescent additive colour, that accumulates the light in well lit places and release the shining effect in very low or no light conditions – i.e. it glows in the dark. Sold with 4-point chin strap included.

Head Protection

Portwest's head protection range aims to benefit our customers by combining the most up to date styles and standards in head protection, irrespective of job or location. Innovative, comfortable and lightweight helmets available for multiple uses.

PPE

Portwest Head PPE range applies the latest standards to deliver the highest level of protection. Comfortable and lightweight, the PPE range will ensure a pleasant wear, even for long periods of use. Your safety is our mission.

Standards

EN 397 (-30°C/+50°C, MM, LD, 440V a.c.) EN 50365 Class:0



Features

- Unvented helmet shell for safe use with electrical applications
- Glow effect in the dark thanks to photo-luminescent additive
- Electrical insulation up to 1000Vac or 1500Vdc (EN 50365)
- 6-point textile suspension harness for enhanced wearer comfort and safety $% \left({{{\left[{{{c_{{\rm{m}}}}} \right]}_{{{\rm{m}}}}}} \right)$
- Size adjustable headband via wheel ratchet system
- Compatible with PS58 helmet visor holder
- Electrical properties (440Vac)
- Compatible with PW47 and PS47 clip-on ear muff
- Chin strap included
- Up to 7 years lifetime from manufacturing date (as long as undamaged)
- CE-CAT III



PRODUCT SPECIFICATION & TECHNICAL DATASHEET

PG54 - Endurance Glowtex Helmet Commodity Code: 6506101000

Test House

INSPEC International B.V. (Notified Body No.: NB: 2849) Beechavenue 54 - 62 , Netherlands Cert No: PPE19161696

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	DUN14
PG54WHR	White	57.0	45.0	46.0	0.5000	0.1180	5036108286379	15036108776525