

### Product data sheet uvex silv-Air 3310 FFP3 NR D



#### Product information

<b>Product features</b>	<ul style="list-style-type: none"><li>• Particle-filtering flat fold mask with exhalation valve</li><li>• Protection level FFP 3</li><li>• Soft material edges for high wearing comfort</li><li>• The adjustable head band offers an easy handling and comfortable fit</li><li>• Exhalation valve reduces breathing resistance and build-up of heat and moisture in the mask</li><li>• Flexible and adjustable nose clip</li><li>• The masks are individually packed</li><li>• Soft sealing lip guarantees a secure, comfortable sealed position of the mask</li><li>• Compatible with uvex safety eyewear</li><li>• Mask fulfils the requirements of the dolomite dust test (D)</li></ul>
<b>Materials</b>	Headband: textile Nose clip: PP Headband clips: PP Filter / mask: Melt Blown PP, Polyester Sealing lip: PVC foam Valve: ABS
<b>Weight</b>	15 g
<b>Standard</b>	EN 149:2001 + A1:2009

#### Versions

Article number	Colour/Version	Retail unit
8733.310	Flat fold mask FFP3, white with valve	15 pcs. per box
8753.310	Flat fold mask FFP3, white with valve	3 pcs. per bag
8753.311	Flat fold mask FFP3, white with valve	2 pcs. per bag

## Packaging sizes

Box	approx. 210 x 130 x 140 mm
Outer Carton	approx. 540 x 440 x 230 mm

## Maximum breathing resistance acc. to EN149 in mbar

	Inhalation resistance 30l/min.	Inhalation resistance 95l/min.	Exhalation resistance 160l/min.
FFP1	0,6	2,1	3,0
FFP2	0,7	2,4	3,0
<b>FFP3</b>	<b>1,0</b>	<b>3,0</b>	<b>3,0</b>

## Areas of use\*

The respiratory protection mask can be used against solid, aqueous and non-volatile liquid aerosols up to <b>30 times</b> the respective limit values.	Woodworking, hard wood, chromium, asbestos (short periods of work), stainless steel, lead, welding, dust that contain beryllium, arsenic, cadmium or cobalt. Medical waste disposal, fungal spores, legionella bacteria, infections, viruses, bacteria, enzyme, nanoparticles.
--	--

\*Please note that the above mentioned areas of use are examples only. The selection of PPE needs to be carried out by a competent person, in conjunction with relevant and current legislation.

All respiratory protective devices fall into PPE category III (high risks).

Uvex accepts no liability for any possible harm or damage which may result from this information.  
This data sheet does not replace a detailed risk assessment nor seeking specialist advice.