

CHRONOSOFT POMPIER

ULTIMATE PROTECTION

Ideal for fire fighting, CHRONOSOFT goggles offer high-end innovation. The elastomer frame withstands extreme heat. The double lens features the EQUALIZER system for effective fog protection.



CHROKADESI




138 g

- + DOUBLE LENS (INNER LENS = ACETATE/OUTER LENS = POLYCARBONATE)**
- + FOR FIRE FIGHTING OR EXTREME TEMPERATURES**
- + LARGE ADJUSTABLE STRAP**

bollé
SAFETY

CHRONOSOFT POMPIER

ULTIMATE PROTECTION

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
CHRONOSOFT POMPIER	Sealed	CHROKADESI	2C-1,2  1 BT 9 KN C€	 EN166 3 4 5 9 BT C€	Anti-scratch(K)/Anti-fog(N)

LENS MARKING

Optical class symbols:

1. Continuous work

Use symbols:

9. Molten metal and hot solids.

Mechanical strength symbols:


B. Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Others symbols:

K. Resistance to surface damage by fine particles (optional)

N. Resistance to fogging (optional)

C€ European standard  Manufacturer name

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

3. Liquid droplets or splashes.


4. Large dust particles > 5 microns.

5. Gas and fine dust particles < 5 microns.

9. Molten metal and hot solids.

B. Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

C€ European standard  Manufacturer name

Bollé Safety product approval certificates to CE standards will be sent on request.

TECHNOLOGY

EQUALIZER

Equalizer is the high performance goggle system for protecting against fog. thanks to its double lens and regulation patch, the equalizer filters and regulates moisture levels in the goggles.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly with a mild soap detergent or optical solution.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: Store between 5 and 40 °, humidity <90%.

PACKAGING AND EAN 13 CODE	
	CHROKADESI
Individual plastic bag and box	3660740000738
60 safety goggles per outer pack	3660740200732

CHARACTERISTICS	
LENSES	PC 1,1 mm (inside) PC 2,1 mm (outside) Curve 6
FRAME	Kraton / TPR
TEMPLES	Non applicable
STRAP	Polyamide, Polyester, Latex
FOAM	No
SPARE LENSES	No



01/10/2013

Europe Bollé Safety
95 rue Louis Guérin
69100 Villeurbanne - France
Tél. : 00 33 (0) 4 78 85 23 64
Fax : 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com

bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park Leatherhead Road - Chessington
Surrey - KT9 2NY
Tél. : 00 44 (0)208 391 4700
Fax : 00 44 (0)208 391 4733
e-mail : sales@bolle-safety.co.uk

bolle
SAFETY