







UPDATED: 23/09/2022

Hantex™ EKOTHERM

Thermal latex grip glove available in HV Orange or HV Yellow

Thick 10gg thermal brushed polyester liner with excellent insulating capacities to keep hands warm in cold environments. High visibility yellow or orange liners for easy recogniton and use in dim lighting applications where being seen is imperative. Crinkle latex coating to the palm offers excellent grip and abrasion resistance in wet and dry applications.

An excellent all-round general handling glove especially popular in the construction industry.



FEATURES AND TECHNOLOGY









HIGH

9GE, United Kingdom (Notified Body No.



TYPICAL INDUSTRIES











WARFHOUSING

HIGHWAYS





BUILDING & CONSTRUCTION

| TECHNICAL | INFORMATION |
|-----------|-------------|

| ORDER REF # | G/HTX-EKOTHERM |
|-------------------------------|---|
| COATING MATERIAL | LATEX |
| PACKING | PER PACK: 10 x Pair |
| | PER CASE: 120 x Pair |
| SIZES AVAILABLE | 8 (M), 9 (L), 10 (XL), 11 (2XL) |
| EU TYPE CERTIFICATION BY | CCQS Certification Services Limited Block 1 Blanchardstown Corporate Park, Ballycoolin Road, Blanchardstown, Dublin15, D15 AKK1, Ireland (Notified Body No. 2834) |
| UKCA TYPE CERTIFICATION BY | CCQS UK Limited 5 Harbour Exchange Square London, E14 |

1105)

CERTIFICATION AND STANDARDS (SEE OVERLEAF FOR FURTHER DETAILS)





- 1 'X' denotes not tested. 2 * Where applicable, EN388:2016 scores take precedent and are
- Nhere appricating, crissions ongoing.
 There is no correlation between coupe test levels and EN ISO 13997 / TDM cut test levels.





CATII UK CE (II





TECHNICAL PRODUCT DATASHEET

COLD PROTECTION




UPDATED: 23/09/2022

CERTIFICATION LEGENDS







^{*} For dulling during cut resistance test (6.2), the coupe test results are only indicative while the TDM cut resistance test (6.3) is the reference performance result.







* For details regarding maximum permissable user exposure, see seperate sheet.

FURTHER INFORMATION

STORAGE / TRANSPORT: Keep away from direct sunlight; store in a cool dry place. Keep away from ozone sources or naked flame. Store the gloves in their original packaging. During transportation, ensure the product is well packaged and protected in order to prevent any damage.

PRECAUTIONS BEFORE USE: 1. Never use these gloves with chemicals. 2. Gloves should not be used when there is a risk of entanglement with moving machine parts. 3. Before usage and periodically during usage, inspect the gloves for any defects or imperfections. Avoid wearing damaged, dirty or worn out gloves. 4. The gloves should not come in contact with a naked flame or fire. 5. Do not subject to high speed or serrated blades. 6. Always read enclosed user instructions before using these gloves. 8. The information provided is for products in a new condition and does not reflect the actual duration of protection in the workplace. 9. Service life cannot be specified and depends on the application and the responsibility of the user to ascertain suitability of the glove for its intended use.

CONSTITUENTS / ALLERGIES: Some gloves may contain ingredients which are known to be a possible cause of allergies in sensitive persons who may develop irritant and/or allergic contact reactions. If an allergic reaction should occur seek medical advice immediately.

WARNING: This product contains natural rubber latex which may cause allergic reactions. If affected, discontinue use immediately and seek medical advice.

¹ Testing carried out on the palm material. Except in cases where the glove is equal to or over 400mm - where the cuff is tested also tested. ² X' denotes Not Tested. ³ Where applicable, EN388.2016 scores take precedent and are ongoing. There is no correlation between coupe test levels and ISO 13997 / TDM cut test levels. Where both EN388.2016 and EN388.2003 scores are shown, the latter is shown for informational purposes only.