

RANGER

INNOVATIVE SAFETY HELMET WITH CRASHBOX IMPACT ABSORPTION SYSTEM



FEATURES

- › Crashbox - the patented, double walled impact absorption system located at the top of the helmet
- › 8 ventilation holes
- › Patented oval shaped slots for attaching hearing or eye/face protection and head light
- › 6-point textile suspension harness
- › Ratchet - easy to adjust even with gloves on
- › Microfibre sweatband
- › 4-point self-releasing chin-strap mounts
- › Adjustable padded headband
- › IntegraSpec - retractable eye protection (optional)

SUITABLE APPLICATIONS

- › Industry, construction and forestry

CERTIFICATION

- › CE
- › EN 397
- › ANSI/ISEA Z89.1 Type 1, Class C



The
Safety Supply
Company

www.thesafetysupplycompany.co.uk

RANGER

TECHNICAL SPECIFICATIONS

TEMPERATURE RESISTANCE	Low temperature -20°C (EN) -30°C (ANSI)
	High temperature +50°C (EN)
SHELL MATERIAL	ABS/Polycarbonate Blend/UV blocker
HARNESS MATERIAL	Polyester
HEADBAND MATERIAL	Polyethylene
SWEATBAND MATERIAL	Microfibre, PU
SLOTS	30mm
WEIGHT	375g
FITTING SIZES	53-62cm
IN-USE LIFETIME	Up to 6 years (if undamaged)

PACKAGING AND MAINTENANCE

CLEANING	Helmet can be hand washed and cleaned with warm soapy water. Chemicals or abrasive cleaners should not be used.
STORAGE	Storage out of direct sunlight in original packaging is recommended.
DISPOSAL	Disposal via normal waste; material is ideal for incineration. Material is not recycled and is not biodegradable.
PACKAGING	1 helmet / box • 6 boxes / case



The
Safety Supply
Company

www.thesafetysupplycompany.co.uk