

**3 AAA** (included)

**XPP-5450G**

**INTRINSICALLY SAFE DUAL-FUNCTION HEADLAMP**

**NIGHTSTICK®**  
*Life Depends on Light™*



Includes a heavy-duty rubber, and a nylon head strap **for use on a hard hat.**



**Single Body Switch.** High-brightness Spotlight, Low-brightness Spotlight



**ANSI IP-67 Dustproof / Waterproof** with a 2 meter drop rating.



**ATEX  
ZONE 0  
IECEx**

**CLASS I  
DIV 1**

**IP-X7  
WATER  
PROOF**



**Adjustable ratchet tilt head** made from an engineered polymer housing



**90 LUMENS**

# INTRINSICALLY SAFE DUAL-FUNCTION HEADLAMP

## 3 AAA INCLUDED

### ITEM NUMBER/UPC

- XPP-5450G, UPC 0 1739880300 7

### MARKET APPLICATIONS

- Hazardous work environments, industrial, automotive, law enforcement, fire & rescue

### CERTIFICATIONS

- cETLus, CE, ATEX, IECEx, Kosha, INMETRO

### CASE MATERIAL

- Engineered Polymer

### SPOTLIGHT LUMENS/RUNTIME

- HIGH: 90L, 13.5 hrs. runtime  
- LOW: 50L, 22.75 hrs. runtime

### CANDELA

- HIGH: 1,615  
- LOW: 1,076

### BEAM DISTANCE

- HIGH: 80m  
- LOW: 65m

### DUST/WATER RATING

ANSI IP-67 Dustproof / Waterproof

### DROP RATING

- 2 meters

### DIMENSIONS

- LENGTH: 2.4 in (61 mm)  
- WIDTH: 1.9 in (48 mm)  
- DEPTH: 1.8 in (46 mm)  
- WEIGHT: 3.5 oz (99 g)

### BATTERY







- 3 AAA (Included)

### WARRANTY

- Limited lifetime warranty

### WHAT'S INCLUDED

- Headlamp  
- 3 AAA batteries  
- Elastic non-slip headband  
- Rubber hardhat strap  
- Instruction manual

FL 1 STANDARD	HIGH	LOW
	90 LUMENS	50 LUMENS
	13h	22h
	80m	65m
	1615cd	1076cd
		
		

**NIGHTSTICK.**

**XPP-5450G**

Bayco Products, Inc. 640 S. Sanden Blvd., Wylie, TX 75098



Intertek  
ID 4003544  
INTRINSICALLY SAFE  
SECURITE INTRINSEQUE



UK  
CA 0359



22-AV480-0216X

SEE INSTRUCTION MANUAL  
VOIR MANUEL

CLASS I DIV 1 GRPS A-D T4  
CLASS II & III GRPS E-G T135C  
CLASS I ZONE 0 AEx ia IIC T4 Ga  
CLASS I ZONE 0 Ex ia IIC T4 Ga  
Ex ia op is IIC T4 Ga  
Intertek ITS 13 ATEX27854X  
ITS21UKEX0247X  
IECEx ITS 17.0002X  
-20°C ≤ Tamb ≤ +40°C  
1.5V/Cell AAA Alkaline

MFG MM-YY

#### CERTIFIED

