HUSTLER **COMBINING STYLE AND PROTECTION**

Water-repellent, the blue flash polarised version repels heat, providing optimum protection and reducing glare. Ideal for off-shore activities. Also available in a smoke version.







HUSTFLASH



Microfibre pouch ETUIFS



- + SIDE SHIELDS
- + NON-SLIP BRIDGE
- + NON-SLIP TEMPLES



HUSTLER COMBINING STYLE AND PROTECTION

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
HUSTLER	Smoke	HUSTPSF	5-3,1 🗁 1 FT CE	🗁 EN166 FT (€	Anti-scratch/anti-fog
	Polarized Blue flash	HUSTFLASH	5-3,1 🗁 1 FT CC	🗁 EN166 FT 🕻 🤆	Anti-scratch/anti-fog

LENS MARKING

Optical class symbols:

1. Continuous work

Mechanical strength symbols:

- F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for glasses.
- The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Others symbols:

C€ European standard ☐ Manufacturer name

TECHNOLOGY

bPOLARIZED

A technology approved for permanent wear and certified with perfect optical quality, it offers unbeatable comfort by filtering glare and reflections. Ideal for the maritime environment. Filters 99.99% of UVA/UVB.

PACKAGING AND EAN13 CODE HUSTPSF HUSTFLASH dividual plastic

bag	3660740006594	3660740006600
10 safety spectacles per inner box	3660740106591	3660740106607
240 safety spectacles per outer pack	3660740206598	3660740206604



Europe Bollé Safety 95 rue Louis Guérin 69100 Villeurbanne - France Tél. : 00 33 (0) 4 78 85 23 64 Fax : 00 33 (0) 4 78 85 28 56 contact@bolle-safety.com

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

- F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for glasses.
- **T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

C€ European standard ☆ Manufacturer name

Bollé Safety product approval certificates to CE standards will be sent on request.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly with a mild soap detergent or optical solution.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: Store between 5 and 40 °, humidity <90%.

CHARACTERISTICS				
LENSES	PC - 2,2 mm - Curve 8			
TEMPLES	Nylon + insert EVA			
STRAP	Non applicable			
FOAM	Non applicable			
SPARE LENSES	No			



e-mail : sales@bolle-safety.co.uk

01/10/2013



bolle-safety.com