

WV100038



Scratch-resistant, and anti-fog polycarbonate eye protection. Attaches with Easy Click Adapters. Securely flips up and down. Available in 3 lens color options for various levels of light transmission.

Compatible with KASK Zenith X Primero and Quantum helmet series.

MOUNTING PARTS



TECHNICAL DETAILS

**STANDARD**
EN ISO 16321
CE
ANSI Z87.1

**CATEGORY**
II


**ENHANCED OPTICAL PERFORMANCE**
1


**MATERIAL**
Polycarbonate


**WEIGHT**
80 g


**LENGTH**
110 mm


TECHNOLOGIES


**ANTI-FOG**
Equipped with an anti-fog treatment to increase wearer visibility when active and in a variety of conditions.


**CUT PROOF EDGE**
Eye shield edge detail designed with a cut proof edge for enhanced wearer safety.

**DRIP PROOF UPPER CONTOUR**
Rubber edge protects eyes from liquid and debris from entering the visor.

**PANORAMIC LENS**
Developed to maximize visibility with minimal viewing distortion.

**COMPATIBLE WITH GLASSES**
Designed for use over corrective glasses.

**ABRASION AND SCRATCH RESISTANCE**
Lens treatment designed with protection from abrasion and scratches or increased durability and viewing clarity.

**EASY CLICK VISOR ADAPTERS**
Requires Easy Click Visor Adaptors to attach to helmet.

CE MARKINGS

CODE	COLOR	MARKING
WV100038-500	CLEAR	ZEN MM/YY CE KASK UL1,2 DT 1 -5°C +55°C K N CH 16321 KASK DT 1-M -5°C +55°C CH
WV100038-510	SMOKE	ZEN MM/YY CE KASK GL1 DT 1 -5°C +55°C K N CH 16321 KASK DT 1-M -5°C +55°C CH
WV100038-520	SILVER MIRROR	ZEN MM/YY CE KASK GL2 DT 1 -5°C +55°C K N CH 16321 KASK DT 1-M -5°C +55°C CH

ANSI MARKINGS

CODE	COLOR	MARKING
WV100038-500	CLEAR	ANSI Z87 + U6 X D3
WV100038-510	SMOKE	ANSI Z87 + U6 L1.5 X D3
WV100038-520	SILVER MIRROR	ANSI Z87 + U6 L2.5 X D3

ADDITIONAL INFORMATION

GUARANTEE
3 years starting from the date of purchase.

LIFE SPAN
10 years starting from the date of manufacture. Life span depends on various factors that can cause deterioration such as sudden temperature changes, the amount of exposure to direct sunlight and the intensity of use. Altered vision and scratches are elements that signal the need to check for deterioration of the visor.

CLEANING
Clean only with water and mild soap. Allow to air dry. Do not use chemical detergents, solvents, petrol powders as they are too aggressive and could lower the structural resistance of the visor.

3
YEARS
GUARANTEE

10
YEARS
LIFE SPAN

 SCAN FOR COMPLETE COLLECTION