

Proximity® ANSI • CE • CSA •



FOAM
PADDING



CO-INJECTED
TEMPLES

Removable flame resistant foam padding // Lightweight spectacle – 26.3gm // Slim co-injected temples // Custom imprinting available

Black Frame | 6 Variations

- SB9310ST ●●● Clear **H2X** AF
- SB9310STM ●●● Clear **H2MAX** AF
- SB9323ST ●● Dark Gray **H2X** AF
- SB9323STM ●● Dark Gray **H2MAX** AF
- SB9330ST ●●● Amber **H2X** AF
- SB9380ST ●●● I/O Mirror AF

Black and Lime Frame | 2 Variations

- SBL9310STM ●● Clear **H2MAX** AF
- SBL9323STM ●● Dark Gray **H2MAX** AF



SB93

Part No.	Lens Marking	Temple Marking
SB9310ST	P Z87 + U6	P Z87 + / P c SEI Z94.3
SB9310STM	P Z87 + U6 X	P Z87 + / P c SEI Z94.3
SB9323ST	P Z87 + S	P Z87 + / P c SEI Z94.3
SB9323STM	P Z87 + S X	P Z87 + / P c SEI Z94.3
SB9330ST	P Z87 + U6	P Z87 + / P c SEI Z94.3
SB9380ST	P Z87 + U6 L1.7	P Z87 + / P c SEI Z94.3
SBL9310STM	P Z87 + U6 X	P Z87 + / P c SEI Z94.3
SBL9323STM	P Z87 + S X	P Z87 + / P c SEI Z94.3

General Specifications
Weight: 26.3 gm
PD: 64 mm
Bridge: 16.5 mm
Lens base: 9.5 curve
Lens size diagonal: 75.8 mm
Lens size vertical: 50.4 mm
Lens thickness: 1.6 mm
Overall length (lens - tip): 161 mm
Overall width (hinge - hinge): 135 mm
Closest point between temple tips: 77 mm
Closest point between lens: 14.5 mm

Materials
Lens: polycarbonate
Temples: polycarbonate & thermoplastic elastomers (TPE)
Hinge: polycarbonate
Screw: stainless steel
Foam gasket: nylon & ethylene-vinyl acetate (EVA) foam

Lens Marking Symbols

P: Manufacturer's mark
Z87: ANSI standard for eye and face protection devices

+: High impact

S: Special Purpose

X: Tested Anti-fog

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L1.7: 55% Max. Visible Light

Temple Marking Symbols

P: Manufacturer's mark
Z87: ANSI standard for eye and face protection devices

+: High impact

c SEI Z94.3: CAN/CSA standard for eye and face protection devices