


Cobra Grade 80 Clevis Self Locking Hook – G80CSLH



- Grade 80 alloy steel.
- Red painted finish.
- Meets the W.L.L. performance requirements of BS EN 1677-3.
- Temp. Range: -20°C up to +200°C.
- Marked with material grade, manufacturers ID, size, product ID mark and traceability code.

Product Code	Part No.	Chain Dia	A	B	C	E	H	L	L1	M	N	Ø
		mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
G80CSLH8	K1801	7/8	9.5	38.5	39	35	29.5	161.8	119.3	87	20	44
G80CSLH10	K1802	10	12.5	48	48	45	30	195	142	108	26	58
G80CSLH13	K1803	13	15	59	65	52.5	40	249	179	122	33	70
G80CSLH16	K1804	16	18.5	77	65	63.3	50.5	310	224.8	168.6	36	86
G80CSLH20	K1805	20	24	81	85	86	55	335	238	185	50	97
G80CSLH22	K1806	22	25	97.5	80	76	67	392	277	202	52	98
G80CSLH26	K1807	26	30	118	125	96	75	449	312	239	60	110

Technical Data

Part No.	Chain Dia	W.L.L.	M.P.L.	M.B.L.	Packing Qty	Weight
	mm	t	t	t		kgs
K1801	7/8	2	4	8	25	0.8
K1802	10	3.15	6.3	12.6	14	1.38
K1803	13	5.3	10.6	21.2	6	2.81
K1804	16	8	16	32	3	6
K1805	20	12.5	25	50	2	7.25
K1806	22	15	30	60	1	12.8
K1807	26	21.2	42.4	84.8	1	21.8