PORTWEST

PRODUCT SPECIFICATION & TECHNICAL DATA

PS63 - Height Endurance Vented Helmet

Collection: Head Protection

Range: PPE Materials: ABS

Product information

Our premium Height Endurance Helmet is now available in a vented version, for extra air flow. Light, comfortable and compact, this peak-less helmet is designed to be used when working at heights. Clever features include an ABS shell, textile comfort 6 points harness, wheel ratchet adjustment, size 52-63cm. Technical sweat band and 4 points chin strap (Y style) with a soft rubber chin protector included.

EN 397 (-30°C / +50°C)

Head Protection

PW rapidly expanding head protection product range aims to benefit our customers by combining the most updated styles and standards in head protection, irrespective of job or location. A wide selection of compatible accessories is also available. A full explanation of features and performances are given in order to help you make a more informed choice.

PPE

Portwest Head PPE range applies the latest standards to deliver the highest level of protection. Comfortable and lightweight, the PPE range will ensure a pleasant wear, even for long periods of use. Your safety is our mission.

Features

- CE certified
- · Light and robust
- Vented hard hat allowing a refreshing airflow around the head
- · Specially designed for working at height
- 6 points textile harness
- · Hi-Visibility colour for visibility in daylight
- Chin strap included
- Compatible with PW47 and PS47 clip-on ear muff
- Compatible accessories available
- 7 years shelf life from manufacturing date outlined in product user sheet



	Range
White	-
Hi-Vis Orange	-
Hi-Vis Yellow	-
Royal	-

PORTWEST_®

PRODUCT SPECIFICATION & TECHNICAL DATA

PS63 - Height Endurance Vented Helmet Commodity Code: 6506101000

Test House

INSPEC International B.V. (Notified Body No.: 2849)

Beechavenue 54-62

1119 PW, Schiphol-Rijk, The Netherlands

Cert No: PPE18161224

CARTON DIMENSIONS/WEIGHT

Item	Colour	Len	Wid	Hgt	Weight (Kg)	Cubic (m³)	EAN13	DUN14
PS63ORR	Orange	57.0	45.0	50.0	0.4500	0.1283	5036108309139	15036108797797