

PW42 - Clip-On Ear Protector

Collection: Ear Muffs

Range: PPE

Materials: HIPS (High Impact Polystyrene), Stainless Steel

Product information

The protectors can be put into the stand off position. Compatible with Expertbase helmets and PW51.

EN 352-3 (SNR 26dB)
ANSI S3.19 (22dB)

Ear Muffs

Portwest Hearing protection range includes PPE with different level sound attenuation, to be adapted to various working environments giving the correct protection from dangerous noise, without isolating the workers. New models and colours for earmuffs allow a personalised choice. An updated range of earplugs complete our competitive and performing offer.

PPE

Portwest Head PPE range applies the latest standards to deliver the highest level of protection. Comfortable and lightweight, the PPE range will ensure a pleasant wear, even for long periods of use. Your safety is our mission.

Features

- CE-CAT III
- Easy to clip-on
- Retail bag which aids presentation for retail sales
- Individually packed for vending machines



	Range
Red	-
Yellow	-

PORTWEST®

PRODUCT SPECIFICATION & TECHNICAL DATA

PW42 - Clip-On Ear Protector Commodity Code: 6506101000

Test House

Michael & Associates, Inc. (Notified Body No.:)
2766 W. College Ave Suite 1
PA 16801, United States
Cert No: Q3932A

BSI Group The Netherlands B.V. (Notified Body No.: 2797)
Say Building, John M. Keynesplein 9, 1066 EP
, Netherlands
Cert No: CE 698123 - I

CARTON DIMENSIONS/WEIGHT

Item	Colour	Len	Wid	Hgt	Weight (Kg)	Cubic (m ³)	EAN13	DUN14
PW42RER	Red	50.0	47.0	52.0	0.2600	0.1222	5036108134670	15036108636249

PERFORMANCES - SOUND ATTENUATION - EN 352-3:2002

PW42/PS42									
A	Frequency (Hz)	63	125	250	500	1000	2000	4000	8000
B	Mean Attenuation (dB)	12.4	14.4	17.9	27.3	34.1	34.8	32.8	32.3
C	Standard Deviation (dB)	5.2	4.9	4.5	4.2	4.2	4.5	4.6	6.4
D	Assumed Protection (dB)	7.2	9.4	13.4	23.1	29.9	30.4	28.2	26.0

SNR 25.9dB H:29.3dB M: 23.8dB L: 15.5dB

PERFORMANCES - SOUND ATTENUATION - ANSI S.19-1974

PW42/PS42										
A	Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000
B	Mean Attenuation (dB)	147.4	20.2	28.0	37.5	34.1	34.6	36.4	35.3	35.0
C	Standard Deviation (dB)	3.1	3.7	3.9	3.8	3.5	3.3	4.0	4.1	4.5

NR (NOISE REDUCTION RATING) = 22dB

ANSI TESTING: Michael & Associates, Inc 246 Woodland Drive, State College, PA 16803

PW42RER