PORTWEST_®

PRODUCT SPECIFICATION & TECHNICAL DATA

BZ12 - Bizweld Cape Hood

Collection: Bizweld[™] Range: Flame Resistant Shell Fabric: Bizweld: 100% Cotton, FR Finish 330g Inner Pack: 10 Outer Carton: 50

Product information

Designed to give maximum protection and comfort to the wearer, the Bizweld cape hood will help keep you safe in dangerous work environments. The cape hood is made with a self fabric drawcord to allow for adjustment for a comforable fit. Must be worn with a suitable coverall or jacket/trouser combination.



Bizweld[™]

The garments in the Bizweld Flame Resistant range have been specially designed to guarantee comfort, performance and safety whilst providing effective function at all times. This range has been rigorously tested to ensure total compliance with the latest international standards.

Flame Resistant

This industry leading flame resistant range provides multi standard protection for hazardous environments. These state of the art products are the result of years of experience combined with advanced technology and market research. Commitment to the health, safety and comfort of the wearer can be seen in the wide range of products suitable for all climates and end uses.

Standards

ELIM TESTING IN PROGRESS EN ISO 11612 (A1+A2, B1, C1, E2, F1) EN ISO 11611 Class 1 (A1+A2) ASTM F1959/F1959M-12 (ATPV 11.2 CAL/CM² (HAF = 80.4%))



Features

- CE-CAT III
- Protection against radiant, convective and contact heat
- Certified protection against molten metal splash
- + 50+ UPF rated fabric to block 98% of UV rays
- Designed with a comfort fit
- Guaranteed flame resistance for life of garment

	Short	Reg	Tall	XTall
Navy		One Size -		

PORTWEST.

PRODUCT SPECIFICATION & TECHNICAL DATA

BZ12 - Bizweld Cape Hood Commodity Code: 6217100090

Test House

SATRA Technology Europe Ltd (Notified Body No.: 2777) Bracetown Business Park D15 YN2P, Ireland Cert No: 2777/12872-02/E00-00



CARTON DIMENSIONS/WEIGHT

Item	Colour	Len	Wid	Hgt	Weight (Kg)	Cubic (m ³)	EAN13	DUN14
BZ12NAR	Navy	43.0	28.0	35.0	0.2400	0.0421	5036108193912	15036108680211