

Product datasheet

uvex 1 x-cite 8640 1-3

Safety shoe DIN EN ISO 20345:2022+A1:2024 S3L FO SR

Sizes: 34 - 44 | Width: 10, 11, 12



AREA OF APPLICATION

The light application covers all areas in which work is carried out indoors in particular and which do not place high demands on the physical properties of the outsole of a safety shoe.

OUTSOLE

Polyurethane outsole



- PU outsole
- antistatic
- short-term heat-resistant up to 120°C
- excellent slip resistance (**SR**)
- oil- and fuel resistant (**FO**)
- free of silicones, plasticisers and other substances that interfere with wetting agents



FEATURES

Upper material	• hydrophobic leather • water-repellent (WPA)
Lining material	• breathable textile (clima zone)
Fastening	• laces
Comfort	• soft padding on collar
Innersole	• removable comfortable innersole
Furthermore	• metal-free

PROTECTIVE FEATURES

Toe cap	• metal-free toe cap with carbon
Penetration resistance	• metal-free, textile penetration resistance

CERTIFICATES

uvex medicare	• certified for orthopaedic innersoles according to the description in DGUV 112-191
ESD	• protection against electrostatic charge according to EN 61340-4-3 und EN 61340-5-1

SUSTAINABILITY

CO ₂ footprint	• 12.95 kg Cradle-to-Customer (calculation date 09/2025)
Recycled/sustainable materials	• penetration resistance and removable innersole made wholly or partly from recycled materials • free from harmful substances in accordance with the uvex restricted substances list

ACCESSORIES/ SPARE PARTS

Replacement innersole	• 8639 7-9
-----------------------	--