RING

SMARTCHARGE PRO 50A BATTERY CHARGER

For workshop and showroom use


















Suitable for















• Up to 50A Continuous charge

POWER SUPPLY:

12V default: 13.4V Max. 50A. Manual adjustable: 12 to 14.9V Max. 50A 24V default: 26.8V Max. 50A. Manual adjustable: 24 to 28.9V Max. 50A

Rapid recharge in minutes

- Stop/Start compatible
- Variable charging rates 12/24V at 5/10/30/50A

For slow or rapid recharge that can get a battery to start in minutes

- 9-Stage charging process for Lead Acid/Gel/AGM/Calcium/EFB batteries
- 9-3-tage charging process for Lead Acid/Gel/Adim/Calcium/EFB batter
- 7-Stage lithium charging process for Lithium batteries
- Large LCD display screen

To see charge status clearly in low light

• Battery and alternator diagnosis

To check potential starting problems and cranking ability

- Pre-charge health check for your engine system
- Easy to use menu system

Making it intuitive to use removing any hassle when working

Removable fully insulated high capacity battery clamps
Provide enhanced user safety



Specifications

| Product Code | RSCP5024 |
|-----------------------|--|
| Voltage Output | 12/24V DC |
| Voltage Input | 220-240V AC |
| Charger Rate | 50A |
| Battery Type | Lead Acid, Gel, Calcium, EFB, AGM & LiFePO4 |
| Max. Battery Capacity | 500Ah |
| Min. Battery Capacity | 14Ah |
| Packaging Dimensions | 407 x 362 x 117mm |
| Pack Weight | 7kg |
| Case Quantity | 2 x 1 |
| Barcode | 5055175249315 |

DESIGNED WITH

THE PROFESSIONAL IN MIND