



Integra® ANSI • CE • CSA •



Adjustable temples ensure reliable performance // Custom imprinting available



SM4

SN4

SNWR4

SR4

Black Frame | 3 Variations

- SB410S ● ● ● Clear
- SB410ST ● ● ● Clear AF
- SB420S ● ● ● Gray

Mixed Blue Frame | 1 Variation

- SM410S ● ● Clear

Blue Frame | 1 Variation

- SN410S ● ● ● Clear

Red, White & Blue Frame | 1 Variation

- SNWR410S ● ● Clear

Red Frame | 1 Variation

- SR410S ● ● Clear

Part No.	Lens Marking	Temple Marking
SB410S	P + U6	P Z87 + / P c SEI Z94.3
SB410ST	P + U6	P Z87 + / P c SEI Z94.3
SB420S	P + U6 L3	P Z87 + / P c SEI Z94.3
SM410S	P + U6	P Z87 + / P c SEI Z94.3
SN410S	P + U6	P Z87 + / P c SEI Z94.3
SNWR410S	P + U6	P Z87 + / P c SEI Z94.3
SR410S	P + U6	P Z87 + / P c SEI Z94.3

General Specifications
Weight: 35 gm
PD: 68 mm
Lens base: 4 curve
Lens size diagonal: 138 mm
Lens size vertical: 39 mm
Lens thickness: 2.0 mm
Overall length (lens - tip): 85 mm
Overall width (hinge - hinge): 149 mm

Materials
Lens: polycarbonate
Side shield: polycarbonate
Frame: nylon 66
Temples: nylon 66
Hinge: polycarbonate
Screw: nickel plated
Nosepiece: polycarbonate

Lens Marking Symbols

- P: Manufacturer's mark
- Z87: ANSI standard for eye and face protection devices
- +: High impact
- S: Special purpose
- 3.0: IR3 lens
- 5.0: IR5 lens

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L3: 18% Max. Visible Light

Temple Marking Symbols

- P: Manufacturer's mark
- Z87: ANSI standard for eye and face protection devices
- +: High impact
- c SEI Z94.3: CAN/CSA standard for eye and face protection devices