



Ultimate Industrial

HAND PROTECTION RANGE



# TECHNICAL PRODUCT DATASHEET

COLD PROTECTION



HEAT PROTECTION



UPDATED: 12/09/2022

## Hantex H2N+

### 3/4 Dual Coated Nitrile Thermal Glove

The Hantex H2N+ consists of a double knitted liner and a dual nitrile foam 3/4 coating. The red polyester outer is enhanced by a premium brushed acrylic inner for excellent thermal insulating properties without compromising on the fit and comfort of the glove.

The 3/4 flat nitrile first coating provides a water proofing layer to keep the hands dry whilst still be able to offer a degree of breathability to the lower hand. The second sandy nitrile palm coating provides the grip by using micro-capillaries to draw liquid and oils away from the surface of the glove and ensuring a stable hold of slippery items.

Tested for contact heat of up to 250deg for up to 15 seconds as part of EN407:2020.

Each pair is retail headercard.



### FEATURES AND TECHNOLOGY



CUT RESISTANT



HEAT TESTED



COLD CONDITIONS



RETAIL PACKAGED



NITRILE FOAM

### TYPICAL INDUSTRIES



GENERAL PURPOSE



MAINTENANCE



RETAIL



LOGISTICS & WAREHOUSING



BUILDING & CONSTRUCTION

### TECHNICAL INFORMATION

ORDER REF #	G/HANTEX-H2N
COATING MATERIAL	Double Coated Nitrile
PACKING	PER PACK: 10 x Pair PER CASE: 100 x Pair
SIZES AVAILABLE	8 (M), 9 (L), 10 (XL), 11 (2XL)
EU TYPE CERTIFICATION BY	CCQS Certification Services Limited Block 1 Blanchardstown Corporate Park, Ballycoolin Road, Blanchardstown, Dublin15, D15 AKK1, Ireland (Notified Body No. 2834)
UKCA TYPE CERTIFICATION BY	CCQS UK Limited 5 Harbour Exchange Square London, E14 9GE, United Kingdom (Notified Body No. 1105)

### CERTIFICATION AND STANDARDS (SEE OVERLEAF FOR FURTHER DETAILS)

EN388:2016



4 2 4 2 X

Abrasion (0-4)  
Cut (0-5)  
Tear (0-4)  
Puncture (0-4)  
TDM Cut (A-F)

EN407:2020



X 2 X X X X

Contact Heat

EN511:2006



X 2 X

Convective Cold (0-4)  
Contact Cold (0-4)

<sup>1</sup> 'X' denotes not tested.  
<sup>2</sup> \* Where applicable, EN388:2016 scores take precedent and are ongoing.  
<sup>3</sup> There is no correlation between coupe test levels and EN ISO 13997 / TDM cut test levels.

CAT II UK CA CE



Ultimate Industrial

HAND PROTECTION RANGE



# TECHNICAL PRODUCT DATASHEET

COLD PROTECTION




HEAT PROTECTION




UPDATED: 12/09/2022

## CERTIFICATION LEGENDS

EN388:2016



EN388:2016  
Blade Cut TDM  
EN ISO 13997 \*



\* For dulling during cut resistance test (6.2), the coupe test results are only indicative while the TDM cut resistance test (6.3) is the reference performance result.

NEWTON LEVEL

≥ 30	F
≥ 22	E
≥ 15	D
≥ 10	C
≥ 5	B
> 2	A

EN407:2020



EN511:2006



\* For details regarding maximum permissible user exposure, see separate sheet.

<sup>1</sup> Testing carried out on the palm material. Except in cases where the glove is equal to or over 400mm - where the cuff is tested also tested. <sup>2</sup> 'X' denotes Not Tested. <sup>3</sup> Where applicable, EN388:2016 scores take precedent and are ongoing. There is no correlation between coupe test levels and ISO 13997 / TDM cut test levels. Where both EN388:2016 and EN388:2003 scores are shown, the latter is shown for informational purposes only.

## FURTHER INFORMATION

**STORAGE / TRANSPORT:** Keep away from direct sunlight; store in a cool dry place. Keep away from ozone sources or naked flame. Store the gloves in their original packaging. During transportation, ensure the product is well packaged and protected in order to prevent any damage.

**PRECAUTIONS BEFORE USE:** 1. Never use these gloves with chemicals. 2. Gloves should not be used when there is a risk of entanglement with moving machine parts. 3. Before usage and periodically during usage, inspect the gloves for any defects or imperfections. Avoid wearing damaged, dirty or worn out gloves. 4. The gloves should not come in contact with a naked flame or fire. 5. Do not subject to high speed or serrated blades. 6. Always read enclosed user instructions before using these gloves. 8. The information provided is for products in a new condition and does not reflect the actual duration of protection in the workplace. 9. Service life cannot be specified and depends on the application and the responsibility of the user to ascertain suitability of the glove for its intended use.

**CONSTITUENTS / ALLERGIES:** Some gloves may contain ingredients which are known to be a possible cause of allergies in sensitive persons who may develop irritant and/or allergic contact reactions. If an allergic reaction should occur seek medical advice immediately.

**WARNING:** This product contains natural rubber latex which may cause allergic reactions. If affected, discontinue use immediately and seek medical advice.

If appropriate to the product, EC/EU Declaration of Conformities, relevant certification and supporting documentation are available to access through your distributor, at the above web address(s) or by contacting UCI customer services quoting the product reference code. This document and any other statement provided herein by or on behalf of UCI are given for informational purposes and do not constitute a contractual agreement nor warranty of merchantability. UCI assumes no responsibility for the suitability or adequacy of an end user's selection of product for a specific purpose. The manufacturer reserves the right to make any modifications it deems necessary. All product and company names are trademarks™ or registered® trademarks of their respective holders. © UCI Limited, 2020