



PRODUCT DATA SHEET

ProSolve® Cable Ties

ProSolve Product Code	Colour	Material	Length (mm)	Width (mm)
PVCT900	Black	Nylon 6.6 UV	900	9
PVCT800	Black	Nylon 6.6 UV	800	9
PVCT700	Black	Nylon 6.6 UV	700	9
PVCT550	Black	Nylon 6.6 UV	550	7.6
PVCT4576	Black	Nylon 6.6 UV	450	7.6
PVCT450	Black	Nylon 6.6 UV	450	4.8
PVCT370	Black	Nylon 6.6 UV	370	7.6
PVCT350	Black	Nylon 6.6 UV	350	4.8
PVCT3076	Black	Nylon 6.6 UV	300	7.6
PVCT300	Black	Nylon 6.6 UV	300	4.8
PVCT250	Black	Nylon 6.6 UV	250	4.8
PVCT200	Black	Nylon 6.6 UV	200	4.8
PVCT150	Black	Nylon 6.6 UV	150	3.6
PVCT100	Black	Nylon 6.6 UV	100	2.5
PVCT900W	White	Nylon 6.6 UV	900	9
PVCT800W	White	Nylon 6.6 UV	800	9
PVCT700W	White	Nylon 6.6 UV	700	9
PVCT4576W	White	Nylon 6.6 UV	450	7.6
PVCT450W	White	Nylon 6.6 UV	450	4.8

PVCT350W	White	Nylon 6.6 UV	350	4.8
PVCT300W	White	Nylon 6.6 UV	300	4.8
PVCT3076W	White	Nylon 6.6 UV	300	7.6
PVCT250W	White	Nylon 6.6 UV	250	4.8
PVCT200W	White	Nylon 6.6 UV	200	4.8
PVCT150W	White	Nylon 6.6 UV	150	3.6
PVCT100W	White	Nylon 6.6 UV	100	2.5

PROPERTIES:

Flammability Rating:	UL94
Temperature Range:	-10°C to +85°C
Ideal Temperature:	(25 ± 5)°C to (60 ± 5)°C
Loop Tensile Strength:	2.5mm – 8.10Kg / 18lbs / 81N 3.6mm – 18.2Kg / 40lbs / 182N 4.8mm – 22.2Kg / 50LBS / 223N 7.6mm – 54.5Kg / 120LBS / 545N 9.0mm – 80.0Kg / 176LBS / 800N

IMPORTANT NOTICE

All statements, technical information and recommendations are based on tests we believe to be reliable as at the date of hereof, but the accuracy or completeness thereof is not guaranteed. Please ensure before using the product that it is suitable for your intended use. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, other than for fraudulent misrepresentation, ProSolve expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.