

# X800

Compatible with all types of helmets, the X800 goggle is perfectly advisable for extreme situations. Lightweight, low profile and fitted with a panoramic lens, the X800 offers increased protection. Ventilated, the X800 goggle offers the best level of fog resistance.

BALLISTIC PC LENS

ANTI-SCRATCH, ANTI-FOG COATINGS

PANORAMIC FIELD OF VISION



PIVOT FOR HELMET WEARERS

BI-MATERIAL COMFORT FRAME

ULTRA VENTILATED FRAME



RX INSERT

ADJUSTBLE LARGE STRAP

106 G

## Ballistic Resistance STANAG 2920

Clear lens: V50 199 m/s (716 km/h)  
Smoke lens: V50 191 m/s (688 km/h)  
Yellow lens: V50 188 m/s (677 km/h)



Version and options

RX INSERT IN OPTION



- SPARE LENSES OPTION:  
- CLEAR, YELLOW AND SMOKE LENSES

SUPPLY WITH: INDIVIDUAL MICROFIBER POUCH +  
INDIVIDUAL RIGID CARRY CASE

# X800

Safety goggles

STANDARD MARKINGS :

Products Ref.	LENSES												FRAMES													
	Risks relating to radiations		Boillé Protection Logo	Optical Quality			Mechanical Risks				Electrical Risks	Thermal Risks	Coatings (Optional marking K: anti-scratch N: anti-fog)	CE logo	Boillé Protection logo	Standards	Chemical Risks			Electrical Risks	Mechanical Risks			Thermal Risks	CE logo	
	EN 170 - UV	EN 172 - Solaires (100% UV)		Permanent Wear	Intermittent Wear	Short Period	Low energy impact 5 m/s	Medium energy impact 120 m/s	High energy impact 190 m/s	Extreme temperature impact	Electric arc short circuiting	Molten metals and hot solids					anti-scratch	anti-fog	Liquid drops	Large dust particles > 5 microns	Gas and fine dust particles < 5 microns	Electric arc short circuiting	Low energy impact 45 m/s	Medium energy impact 120 m/s		High energy impact 190 m/s
X800I	2C-1.2			1			B	N/A	T	N/A	N/A					EN 166				N/A		B	N/A	T	N/A	
FAX8I	2C-1.2			1			B	N/A	T	N/A	N/A				N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
FAX8J	2C-1.2			1			B	N/A	T	N/A	N/A				N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
FAX8F		5-2.5		1			B	N/A	T	N/A	N/A				N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

N/A: Non Authorized in the standards

**TACTICAL**  
Ballistic resistance  
STANAG 2920



SOSX800



FAX8I

V50 : 716 km/h (199 m/s)



FAX8J

V50 : 677 km/h (188 m/s)



FAX8F

V50 : 688 km/h (191 m/s)

CHARACTERISTICS :

Lens	Clear PC - 2.8 mm - Curve 5.25
Frame	Bi-material (Nylon + TPE)
Spare Lenses	Available in clear, smoke and yellow
Strap	Adjustable, 35 mm wide in nylon
Foam	No
Case	Black

PACKAGING AND EAN 13 CODE :

	X800I
individual carry case	3660740002749
N/A	N/A
60 safety goggles per outer pack	3660740202743

PACKAGING AND EAN 13 CODE :

	FAX8I	FAX8J	FAX8F
individual carry case	3660740001575	3660740001582	3660740001568
30 spare lenses per inner box	3660740101572	3660740101589	3660740101565
300 spare lenses per outer pack	3660740201579	3660740201586	3660740201562

Notified laboratories for certification :



Banc Officiel d'Epreuve Saint-Etienne

