

X1000

RESISTANCE & COMFORT

The X1000, our iconic ballistic goggles, are designed to meet all your needs. Its interchangeable CSP lenses options, each featuring our exclusive PLATINUM anti-fog and anti-scratch coating, are suited for various tactical scenarios. Compatible with all military equipments, it guarantees comfort, stability, and reliable protection, even during extended missions. With a matte black vented or sealed frame, the goggles are available as a military kit or a single unit system. The X1000 is the optimal choice for operators seeking maximum performance in extreme situations or challenging environments.

SUPPLIED WITH : KIT (Box, case, microfiber pouch, user instruction)

 **106 G**

- + **CRYSTAL-CLEAR VISION WITH PLATINUM: ANTI-SCRATCH & ANTI-FOG COATING**
- + **HIGH-IMPACT BALLISTIC PROTECTION: MIL & STANAG**
- + **QUICK AND EASY LENS REPLACEMENT**
- + **PIVOT FOR HELMET WEARERS - QUICK RELEASE SYSTEM**



TECHNOLOGIES

CSP

PLATINUM

VERSIONS



X1000T10M



X1000T11M



X1000T70M



X1000T00M

































X1000T01M



X1000T02M



X1000T03M

X1000						
REFERENCE	VERSION	LENS MARKING	FRAME MARKING	BALLISTIC RESISTANCE V50 STANAG 2920	MIL-PRF	COATING
 X1000T10M	 CLEAR VENTED	 UL1.2 DT 1 KN CE	16321  UL1.2 GL2 DT 1-M 3 6 CE 	867,6KM/H - 241M/S	32432A	 PLATINUM
 X1000T11M	 CLEAR SEALED	 UL1.2 DT 1 KN CE	16321  UL1.2 GL2 DT 1-M 3 6 4 5 CE 	867,6KM/H - 241M/S	32432A	 PLATINUM
 X1000T70M	 CLEAR AMBER SMOKE VENTED	CLEAR:  UL1.2 DT 1 KN CE SMOKE:  GL2 DT 1 KN CE AMBER:  UL1.2 DT 1 KN CE	16321  UL1.2 GL2 DT 1-M 3 6 CE 	CLEAR: 867,6KM/H - 241M/S SMOKE: 871,9KM/H - 242,2M/S AMBER: 879,1KM/H - 244,2M/S	32432A	 PLATINUM
	X1000T00M	 CLEAR	 UL1.2 DT 1 KN CE	867,6KM/H - 241M/S	32432A	 PLATINUM
	X1000T01M	 AMBER	 UL1.2 DT 1 KN CE	879,1KM/H - 244,2M/S	32432A	 PLATINUM
	X1000T02M	 SMOKE	 GL2 DT 1 KN CE	871,9KM/H - 242,2M/S	32432A	 PLATINUM
BOLLÉ SAFETY PRODUCT APPROVAL CERTIFICATES TO CE STANDARDS WILL BE SENT ON REQUEST.						

BALLISTIC STANDARDS

STANAG
2920

MIL-PRF
32432A

GENERAL SPECIFICATIONS			
LENS	POLYCARBONATE - 3MM - CURVE 5	CE	ISO 16321
FRAME	TPV - SANTOPRENE - VENTED - INDIRECT VENTILATION - BREATHABLE FOAM	ANSI	ANSI Z87.1-2020
STRAP	NYLON POLYESTER - 35MM	AS/NZS	

OPTIONAL ACCESSORIES

REFERENCE	DESCRIPTION	SINGLE:	INNER BOX:	OUTER PACK:
X1000T03M	RX INSERT - PC CLEAR	3660740020316	3660740120313	3660740220310

KNOW MORE ABOUT MARKINGS:

OR SCAN:



PACKAGING & EAN13 CODE

SINGLE:	INNER BOX: Size: 24,3 x 18,3 x 9 cm Weight: 0.45 kg	OUTER PACK: Size: 58 x 38 x 30 cm Weight: 8.9 kg
3660740020279		3660740220273 - 36 pcs
3660740021429		3660740221423 - 36 pcs
3660740020262		3660740220266 - 22 pcs
3660740020286	3660740120283 - 15 pcs	3660740220280 - 120 pcs
3660740020293	3660740120290 - 15 pcs	3660740220297 - 120 pcs
3660740020309	3660740120306 - 15 pcs	3660740220303 - 120 pcs
CUSTOM CODE: 9004901000		



MADE IN: TW

DATASHEET: 03-19-2025

CLEANING & STORAGE

CLEANING : The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE : Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE : All products must be stored in a dry and clean environment.

